

CLAIMS

What is claimed is:

- 5 1. A method for grooming network traffic in a digital cross connect,
 comprising: grooming inbound traffic at a first transport switch for at least one
 local switch; and grooming outbound traffic at a second transport switch for the
 at least one local switch.
- 10 2. The method according to Claim 1 wherein the grooming of inbound and
 outbound traffic is performed independently.
3. The method according to Claim 2 wherein the grooming of inbound and
 outbound traffic is performed free of tandem tying the first and second transport
15 switches.
4. The method according to Claim 1 further including configuring the at least one
 local switch to operate with the first and second transport switches.
- 20 5. The method according to Claim 1 further including performing protocol
 switching at the at least one local switch.
6. The method according to Claim 1 further including performing grooming at at
 least a third transport switch.
- 25 7. The method according to Claim 1 wherein the first and second transport
 switches are at least one of the following:
 wideband crossconnect switches, narrowband crossconnect switches, or
 broadband crossconnect switches.

8. The method according to Claim 1 performed in a central office.
9. The method according to Claim 1 performed in an electrical, optical, or wireless network.
- 5 10. A system for grooming network traffic in a digital cross connect, comprising:
a first transport switch that grooms inbound traffic for at least one local switch; and
a second transport switch that grooms outbound traffic for the at least
10 one local switch.
11. The system according to Claim 10 wherein the first transport switch and second transport switch operate substantially free of intermachine tandem ties.
- 15 12. The system according to Claim 10 wherein the local switch is configured to operate with the first and second transport switches.
13. The system according to Claim 10 wherein the local switch is a protocol switch.
- 20 14. The system according to Claim 10 further including a third transport switch that grooms other traffic.
15. The system according to Claim 10 wherein the transport switches are at least one of the following: a wideband crossconnect switch, narrowband crossconnect
25 switch, or broadband crossconnect switch.
16. The system according to Claim 10 used in a central office.
17. The system according to Claim 10 used in an electrical, optical or wireless
30 network.

18. A system for grooming network traffic in a digital cross connect, comprising:
- means for grooming inbound traffic at a first transport switch for at least one local switch; and
 - 5 means for grooming outbound traffic at a second transport switch for the at least one local switch, the first transport switch being distinct from the second transport switch.